

Final Report

Adaptive Computation and Modeling for Multiscale Analysis

Contract Number DAAD 19-01-1-0655

Joseph E. Flaherty
and
Mark S. Shephard

Scientific Computation Research Center
Rensselaer Polytechnic Institute
Troy, New York 12180, USA

DISTRIBUTION STATEMENT A
Approved for Public Release
Distribution Unlimited

20050711 098

REPORT DOCUMENTATION PAGE

Form Approved
OMB NO. 0704-0188

Public Reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimates or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188,) Washington, DC 20503.

1. AGENCY USE ONLY (Leave Blank)		2. REPORT DATE May 3, 2005		3. REPORT TYPE AND DATES COVERED Final (6/1/01-11/30/04)	
4. TITLE AND SUBTITLE Adaptive Computation and Modeling for Multiscale Analysis				5. FUNDING NUMBERS Grant No. DAAD19-01-1-0655	
6. AUTHOR(S) Joseph E. Flaherty and Mark S. Shephard					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Rensselaer Polytechnic Institute 110 8 th Street Troy, NY 12180				8. PERFORMING ORGANIZATION REPORT NUMBER J11148Final	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U. S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211				10. SPONSORING / MONITORING AGENCY REPORT NUMBER 41645.1-MA	
11. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.					
12 a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12 b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Algorithms and software for the adaptive solution of multiscale problems involving partial differential equations and linkage to atomic level simulations. Efforts focused on techniques for using the discontinuous Galerkin method to solve hyperbolic and singularly perturbed parabolic problems. New anisotropic adaptive and parallel solution techniques, <i>a posteriori</i> error estimation strategies, limiting procedures that reduce spurious oscillations near discontinuities, and discontinuity detection strategies that reduce the need for limiting, thereby reducing both excess diffusion and spurious oscillations were developed. The software and methods are being tested on a variety of problems involving compressible flows. In collaboration with engineers at Benét Laboratories, we have been investigating muzzle blast from cannons with perforated brakes. A new procedure to couple atomic/continuum level adaptive simulations was developed and demonstrated on test problems. Scale error indicators have developed and adaptive construction of local atomic regions demonstrated.					
14. SUBJECT TERMS Multiscale simulation Adaptive methods Discontinuous Galerkin Methods				15. NUMBER OF PAGES 9	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OR REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION ON THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

NSN 7540-01-280-5500

Standard Form 298 (Rev.2-89)
Prescribed by ANSI Std. Z39-18
298-102

Statement of Problem Studied

Algorithms and software for the adaptive solution of multiscale problems involving partial differential equations and linkage to atomic level simulations were researched. Techniques for using the discontinuous Galerkin method to solve hyperbolic and singularly perturbed parabolic problems were developed. New anisotropic adaptive and parallel solution techniques, *a posteriori* error estimation strategies, limiting procedures that reduce spurious oscillations near discontinuities, and discontinuity detection strategies that reduce the need for limiting, thereby reducing both excess diffusion and spurious oscillations were developed. The software and methods are being tested on a variety of problems involving compressible flows. In collaboration with engineers at Benét Laboratories, we have been investigating muzzle blast from cannons with perforated brakes.

A new procedure to couple atomic/continuum level adaptive simulations was developed and demonstrated on test problems. Scale error indicators have developed and adaptive construction of local atomic regions demonstrated.

Summary of Most Important Results

Discontinuous Galerkin Methods

An adaptive software system for solving multiscale hyperbolic conservation laws by the discontinuous Galerkin (DG) method has been developed. The software is capable of addressing problems in one, two, and three spatial dimensions using anisotropic adaptive *h*-refinement.

The DG method offers several advantages relative to traditional finite element and finite volume methods when solving hyperbolic systems of conservation laws. The advantages and several aspects of the DG method are described in a sequence of manuscripts that construct orthogonal bases [18,21], describe limiting procedures [10], develop efficient local time stepping algorithms [5,18], create efficient serial and parallel data representations [20], and apply the method to compressible flow problems [2,3,18,22].

In order to guide adaptive enrichment and appraise the accuracy of computed solutions, we developed *a posteriori* estimates of discretization errors. We show [1, 9] that the leading term of the spatial discretization error of a piecewise-polynomial solution of degree p is the difference between orthogonal polynomials of degrees p and $p + 1$. In one dimension, the orthogonal polynomials are Radau polynomials and in two dimensions on triangular elements they are linear combinations of Dubiner polynomials. We further demonstrate a strong superconvergence at downwind element boundaries where the average spatial error converges as $O(h^{2p+1})$ [9].

The strong superconvergence at outflow boundaries can be used to identify discontinuities. This, in turn, can be used to provide information on where to apply limiting to reduce oscillations when using high-order methods. This procedure has been remarkably successful at reducing both excess dissipation and spurious oscillations near discontinuities [10].

To increase the effectiveness of the adaptive procedures a set of anisotropic adaptive mesh control technologies have been developed. The two key components of this procedure are anisotropic correction indication procedures and anisotropic mesh adaptation procedures. The anisotropic correction procedure has two major components [22] that construct a anisotropic mesh metric tensor over the problem domain. In smooth portions the mesh metric tensor employs the Hessian of the solution field [12,13,22]. The portions of the domain that are not smooth employ the shock capturing procedure of reference [10]. In these locations the mesh metric tensor is defined to align with the shocks and to blend into the smooth portions of the domain [22]. The anisotropic mesh adaptation is carried out using a complete set of mesh modification operations for anisotropic meshes [12,13] and fully account for curved domain boundaries [11].

Figures 1 and 2 show a 2-D and 3-D result obtained with the adaptive anisotropic adaptive DG procedure just described.




Figure 1. The meshes and pressure contours for $t=0.0$, $t=0.0002$ and $t=0.0005$ in a 2-D Muzzle blast simulation.




Figure 2. Mesh and pressure contours of a 3-D blast problem.

Level Set Method for Solving Fluid/Rigid body Interaction Problems

The simulation of flow problems with moving objects require an effective means to account for the motion of the object through the domain of the mesh. A level set based method that allows the object to move through the mesh has been developed to allow rigid objects to move through a mesh. In this method an Eulerian mesh is created over the entire computational domain [6]. The movement of the rigid object will cut some of the mesh entities and introduce new boundaries inside the fluid. The level set technique is used to track the interface between the rigid body and the compressible fluid, and the Ghost Fluid Method (GFM) to capture the correct boundary condition implicitly at the interface. Therefore, handling the boundaries is simplified and we have the advantage of doing a fluid calculation on the entire domain. By doing this, we can handle the contribution of the embedded moving boundaries in the fluid without mesh modification.

For the elements in the Eulerian mesh, there are two different possible cases according to their position with respect to the zero level set of the level set function. Case (i), the entity is totally outside the zero level set. Case (ii), the entity is totally inside the zero level set or the entity is cut by the zero level set. For all entities of case (i), the object in the fluid has no direct effect on this entity, so no special operations are needed. For all entities of case (ii), the boundary of the fluid/solid interface must be accounted for using the GFM to capture the correct boundary conditions. The level set enables us to locate those entities that need special treatment, even when we do not know the position of the precise position of the moving boundary in the entity. Actually, we also do not want to find the precise position of the moving boundary because it is an expensive operation, especially for high order approximation and for high dimension case.

We treat the rigid body moving in a fluid as a contact discontinuity at the interface because the fluid near the interface will move with the velocity of the rigid body. The Rankine-Hugoniot

jump conditions imply that both the pressure and the normal velocity are continuous across the interface. Therefore, we set the values for the *ghost entity* to enforce these two conditions. There are three kinds of state variables that need to be set: velocity, density, energy (or pressure). At the same time, since the interface of the rigid body acts as a reflective wall boundary for the fluid, a reflective constraint can capture the boundary condition. For DGM, ghost values are set at every *ghost entity* by considering and setting the values at every gauss point inside the rigid object.

This approximation is straightforward even in the multi-dimensional case. This is an advantage because we can treat the one-, two- and three-dimensional cases with the same scheme and the numerical implementation is simple and consistent for all cases. On the other hand, a lot of reflective points may need to be searched. To speed the procedure, an octree data structure is designed and implemented. In the case that a reflective point does not belong to the computational domain of the problem, specific care must be taken in setting values.

This procedure has been combined with adaptive mesh refinement [21,22] to control solution errors to solve problems with moving objects (see Figure 3).




Figure 3. Example sphere moving through a fluid domain.

Coupled Atomistic-Continuum Simulations

We have developed a Composite Atomistic-Continuum Method (CACM) for multiscale analysis of coupled discrete and continuum models [5]. The main idea of the method is to use atomistic analysis only at places where needed to capture the highly nonlinear behavior and continuum analysis will be used elsewhere for efficiency. Such a method permits the explicit representation of the nano-scale physics. The components of the CACM and its development include:

1. *CACM Method:* In CACM, the continuum is represented by linear elasticity model, and discretized using finite elements on a coarse grid. An atomistic representation in the regions of high field gradients or where the highly nonlinear and non-local behavior of the lattice is important, *i.e.*, at the places where there is nucleation or close range interaction of the defects is used. In these regions, an atomistic grid is used which carries the boundary conditions imposed by the continuum and returns to the continuum correcting information. The atomistic grid is defined in restricted spatial regions and

relocates with the defects. This procedure minimizes the computational effort associated with atomistic simulations, while insuring the required accuracy at relevant spatial locations. We have tried various algorithms, and operators to link the two scales. Based on the effectiveness, meaningfulness and ease of transferring the information from the continuum to the atomistic, and back to the continuum, at this point we have selected to transfer the displacement information from the continuum to the atomistic as the boundary condition for the atomistic analysis. Then in turn the atomistic analysis provides the correction of the continuum solution at the critical places. The atomistic grid is overlaid on the continuum grid, and this method doesn't have the restriction of matching the two grids. This allows for using quite coarse grid at the continuum level unlike some other methods, which is forced to use refined meshes for the continuum near the atomistic regions to match the atomistic grid.

2. *Implementation of the CACM:* The algorithm for the CACM was implemented in the environment of Trellis, a framework for 3D adaptive multi-physics and multi-scale analysis. The Trellis framework was extended to build the scope for multiscale applications. The capability to solve 3D atomistic problems using various types of potentials was implemented within the Trellis framework. To couple the continuum analysis with the atomistic analysis a module responsible for transferring the information between the two analyses was implemented. This module has been implemented in a general manner so as to be able to be utilized for possible coupling of other analyses.
3. *Error indicators:* We have identified the following three criterions required for the adaptive selection of the model:
 - (a) Non linearity: This is characterized by the magnitude of the strain. We have already developed an error indicator to capture this property. The error indicator is based on the relative magnitude of the first order energy term in comparison to the zeroth order term.
 - (b) Non locality: This is characterized by the gradient of the strain. Indicators to capture this information were proposed, and used effectively in their method.
 - (c) Non-convexity: This is characterized by the change in energy felt by the continuum once a defect passes through it.
4. *Adaptive modeling:* The software has to be generalized in the following respects to handle adaptivity: (a) Building a module that will provide indicators of the error in modeling. (b) Automatic generation of the discrete regions based on the error information.
5. *Demonstration of the CACM:* Figure 4 shows an example of the multiscale modeling of the growth of defects at a crack tip [5].

Technology Transfer

Joseph E. Flaherty and Mark S. Shephard have regular interactions with Robert Dillon, Deborah Bleau, and Daniel Cler of Benét Laboratories [2,3]. As described in Section 1, we have been collaborating on using the DG software to analyze muzzle blast effects with large-calibre weapons systems. These problems involve complex three-dimensional interior and exterior flows including realistic geometries and ground reflections.




Figure 4. Example of the multiscale modeling of the growth of defects at a crack tip.

J. E. Flaherty was also the dissertation advisor (with Henry Nagamatsu) of Eric Kathe, a mechanical engineer at Benét Laboratories. Dr. Kathe completed his Ph.D. dissertation in May 2002.

A start-up company, Simmetrix Corporation, is building on the mesh modification and analysis framework developments done in this project. Simmetrix has commercialized a number of the mesh generation and mesh adaptation procedures developed in this project. They have also obtained two ARMY supported SBIR's. The first is concerned with the development of commercial parallel adaptive simulation technologies. The second, which has just recently started is concerned with the development of multiscale simulation technologies with an

emphasis on atomic level simulation model generation and control. Rensselaer is a sub-contractor to Simmetrix on both of these SBIR's.

Publications from this Work and References Cited Above

- [1] Adjrid, S., Devine, K.D., Flaherty, J.E., and Krivodonova, L., "A posteriori error estimation for discontinuous Galerkin solutions of hyperbolic problems", *Computer Methods in Applied Mechanics and Engineering*, 191 (2002), 1997-1112.
- [2] Cler, D.L., Chevaugeon, N., Shephard, M.S., Flaherty, J.E. and Remacle, J.-F., "CFD application to gun muzzle blast - A validation case study", *41st AIAA Aerospace Sciences Meeting and Exhibit*, Jan. 2003.
- [3] Chevaugeon, N., Hu, P., Li, X., Xin, J., Cler, D., Flaherty, J.E. and Shephard, M.S., "Discontinuous Galerkin methods applied to shock and blast problems", *Journal of Scientific Computing*, 22:227-243, 2005.
- [4] Datta, D., Picu, R.C. and Shephard, M.S., "Composite Grid Atomistic Continuum Method: An adaptive approach to bridge continuum with atomistic analysis", *Journal of Multiscale Computational Engineering*, 2(3):401-420, 2004.
- [5] Flaherty, J.E., Krivodonova, L., Remacle, J-F. and Shephard, M.S., "Aspects of discontinuous Galerkin methods for hyperbolic conservation laws", *Finite Elements in Analysis and Design*, 38 (2002), 889-908.
- [6] Hu, P., Flaherty, J.E. and Shephard, M.S., "Solving Fluid/Rigid body Interaction Problem by a Discontinuous Galerkin Level Set Method", in preparation.
- [7] Korneev, V., Flaherty, J.E., Oden, J.T., and Fish, J., "Additive Schwarz algorithms for solving hp-version finite element systems on triangular meshes", *Applied Numerical Mathematics*, 43 (2002), 399-421.
- [8] Korneev, V., Flaherty, J.E., Oden, T., and Fish, J., "Hp-version additive Schwarz algorithms on triangular meshes", *Mathematics Modeling*, 14 (2002), 61-94.
- [9] Krivodonova, L. and Flaherty, J.E., "Error estimation for discontinuous Galerkin solutions of multidimensional hyperbolic problems", *Advances in computational mathematics*, 2003, to appear.
- [10] Krivodonova, L., Xin, J., Remacle, J.-F., Chevaugeon, N., and Flaherty, J.E., "Shock detection and limiting with discontinuous Galerkin methods for hyperbolic conservation laws", *Applied Numerical Mathematics*, submitted, 2003.
- [11] Li, X., Shephard, M.S. and Beall, M.W., "Accounting for curved domains in mesh adaptation", *International Journal for Numerical Methods in Engineering*, 58:246-276, 2003.
- [12] Li, X., Shephard, M.S. and Beall, M.W., "3-D Anisotropic Mesh Adaptation by Mesh Modifications", to appear, *Comp. Meth. Appl. Mech. Engng.*, 2005.
- [13] Li, X., Remacle, J.-F., Chevaugeon, N. and Shephard, M.S., "Anisotropic Mesh Gradation Control", *13th International Meshing Roundtable*, Sandia National Laboratories, SAND #2004-3765C, pp. 401-412, 2004.
- [14] Luo, X., Shephard, M.S. and Remacle, J.-F., "The influence of geometric approximation on the accuracy of high order methods", *Proc. 8th International Conference on Numerical Grid Generation in Computational Field Simulations*, Mississippi State University, Starkville, 2002.

- [15] Luo, X., Shephard, M.S., Remacle, J.-F., O'Bara, R.M., Beall, M.W., Szabó, B.A. and Actis, R., "P-Version mesh generation issues", *11th International Meshing Roundtable*, Sandia National Laboratories, Albuquerque, 343-354, 2002.
- [16] Luo, X.-J., Shephard, M.S., O'Bara, R.M., Nastasia, R. and Beall, M.W., "Automatic p-version mesh generation for curved domains", *Engineering with Computers*, 20(3):273-285, 2004.
- [17] Remacle, J.-F. and Shephard, M.S., "An algorithm oriented mesh database", *International Journal for Numerical Methods in Engineering*, 58:349-374, 2003.
- [18] Remacle, J.-F., Flaherty, J.E. and Shephard, M.S., "An adaptive discontinuous Galerkin technique with an orthogonal basis applied compressible flow problems", *SIAM Review*, 45(1):53-72, 2003.
- [19] Remacle, J.-F., Klass, O., Flaherty, J.E., and Shephard, M.S., "A parallel algorithm oriented mesh database", *Engineering with Computers*, 18(3):274-284, 2002.
- [20] Remacle, J.F., Shephard, M.S. and Flaherty, J.E., "Some issues on distributed mesh representations", *Proc. 8th International Conference on Numerical Grid Generation in Computational Field Simulations*, Mississippi State University, Starkville, 2002.
- [21] J.-F. Remacle, X. Li, M.S. Shephard, and N. Chevaugeon, "Transient mesh adaptation using conforming and non-conforming mesh modifications," *11th International Meshing Roundtable*, Sandia National Laboratories, Albuquerque, 261-272, 2002.
- [22] Remacle, J.-F., Li, X., Shephard, M.S. and Flaherty, J.E., "Anisotropic Adaptive Simulation of Transient Flows using Discontinuous Galerkin Methods", *International Journal for Numerical Methods in Engineering*, 62:899-923, 2005.
- [23] Shephard, M.S., Flaherty, J.E., Jansen, K.E., Li, X., Luo, X.-J., Chevaugeon, N., Remacle, J.-F., Beall, M.W. and O'Bara, R.M., "Adaptive mesh generation for curved domains", *J. for Applied Numerical Mathematics*, 53(2-3)251-271, 2005.
- [24] Zeghal, M., El Shamy, U., Shephard, M.S., Dobry, R., Fish, J. and Abdounm T, "Micro-mechanical analysis of saturated granular soils", *Journal of Multiscale Computational Engineering*, 1(4):441-460, 2003.

Scientific Personnel

In addition to the Principal Investigators Joseph E. Flaherty and Mark S. Shephard, former Ph.D. scholar Lilia Krivodonova and Ph.D. students Peng Hu, Jamal Faik, Viswanath Ramakkagari and Jianguo Xin have also received support. Dr. Krivodonova completed her Ph.D. dissertation in August 2002 and is currently a Postdoctoral Fellow at New York University's Courant Institute of Mathematical Sciences. Dr. Xin completed his thesis in April of 2005, and Peng Hu, Jamal Faik and Viswanath Ramakkagari are writing their thesis'.

Inventions

No patents were filed based on this work.